

Xerox® VersaLink® C7000 Colour Printer



Single Tray Module



Integrated Office Finisher



Single Tray with Stand



Three Tray Module

The VersaLink C7000 Colour Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK C7000DN
One-Sided Speed¹ 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 35 ppm (pages per minute) long edge feed (LEF) Up to 22 ppm Up to 19 ppm
Two-Sided Speed¹ 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	35 ppm (pages per minute) LEF Up to 14 ppm Up to 13 ppm
Monthly Duty Cycle²	Up to 153,000 pages / month
Recommended Average Monthly Print Volume³	Up to 10,000 pages
Hard Drive	320 GB HDD (Optional)
Processor	1.05 GHz Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

Xerox® VersaLink® C7000 Colour Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V -10% / +6% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 8 A			
POWER CONSUMPTION				
Printing ⁴	For 110V: 1.6 kWh For 220V: 1.6 kWh			
Standby Mode ⁴	110V: 94 watts or less 220V: 94 watts or less			
Sleep Mode ⁴	110V: 1.0 watts or less 220V: 1.4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.75 B(A) or less Standby: 4.10 B(A) or less Full System (including finisher) Printing: 7.52 B(A) Standby: 4.10 B(A)			
Sound Pressure Levels	Printing: 52.5 dB(A) Standby: 26.0 dB(A) Full System (including finisher) Printing: 60.0 dB(A) Standby: 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	23.23 in. / 590 mm	26.41 in. / 670.8 mm	25.08 in. / 637 mm	119.71 lb. / 54.3 kg
Base Unit with Single Tray with Stand Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	171.08 lb. / 77.6 kg
Base Unit with Three Tray Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	178.75 lb. / 81.8 kg
Base Unit with Three Tray Module and Integrated Office Finisher	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	215.17 lb. / 97.6 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				

Xerox® VersaLink® C7000 Colour Printer

PRINT	
First-print-out Time	As fast as 7.6 seconds colour
	As fast as 5.1 seconds black-and-white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper
Print Features	<ul style="list-style-type: none"> Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default – DN configuration) Watermark (predefined and custom) Earth Smart Driver Settings
Print from USB	<ul style="list-style-type: none"> Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	<ul style="list-style-type: none"> Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® <p>Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.Support.Xerox.com.</p>

Xerox® VersaLink® C7000 Colour Printer

Fonts	PostScript fonts: 136 PCL fonts: 83
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
Mopria® Certified	ConnectKey Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the device.

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
	*Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNTING / NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device print usage • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements include simultaneous support for HTTP/HTTPS protocols • Device requests account authentication from third party server enabling larger databases of users and accounts • Accept Authentication Login at control panel and pass to third party Networking Account

Xerox® VersaLink® C7000 Colour Printer

PAPER HANDLING			
BYPASS TRAY			
Capacity⁵	100 sheets		
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 216 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm		
Media Types	Bond Plain Paper Cardstock Custom Envelopes	Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
TRAY 1			
Capacity⁵	520 sheets		
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm		
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm		
Media Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
SINGLE TRAY MODULE (OPTIONAL)			
Capacity⁵	520 sheets		
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm		
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm		
Media Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
SINGLE TRAY MODULE WITH STAND (OPTIONAL)			
Capacity⁵	520 sheets		
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm		
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled

Xerox® VersaLink® C7000 Colour Printer

THREE TRAY MODULE (OPTIONAL)			
Capacity⁵	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets		
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm		
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched	Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)			
Capacity⁵	Up to 60 envelopes		
Sizes	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm		
Weights	20 lb. bond to 25 lb. bond / 75 to 90 gsm		
TOTAL CAPACITY			
Base Unit Capacity⁵	620 sheets		
Single Tray Module Capacity⁵	1,140 sheets		
Single Tray Module with Stand Capacity⁴	1,140 sheets		
Three Tray Module Capacity⁵	2,180 sheets		
FINISHING			
OUTPUT TRAYS			
Center Output Catch Trays	500 sheets; tray offsets		
INTEGRATED OFFICE FINISHER (OPTIONAL)			
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3		
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm		
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm		
Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		

Xerox® VersaLink® C7000 Colour Printer

REMOTE CONTROL PANEL		
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device 	
XEROX® CENTREWARE® WEB		
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE		
Device Status	<ul style="list-style-type: none"> • Tray status/contents • Consumables status • Billing/Usage • Quick Links • Online Support 	
Print Queue Viewing	Job print queue management—view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
WHAT COMES IN THE BOX		
	<ul style="list-style-type: none"> • VersaLink C7000 Colour Printer • Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 3,300 print capacity⁶, Black: 5,300 print capacity⁶ • Imaging Drum – One of each (Cyan, Magenta, Yellow, Black): 82,200 print capacity⁶ • Quick Use Guide • Quick Install Guide • Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement) • Power Cord 	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Print Cartridges	Cyan: 3,300 standard pages ⁶ Magenta: 3,300 standard pages ⁶ Yellow: 3,300 standard pages ⁶ Black: 5,300 standard pages ⁶	106R03772 106R03771 106R03770 106R03769

Xerox® VersaLink® C7000 Colour Printer

High Capacity Print Cartridges	Cyan: 10,100 standard pages ⁶ Magenta: 10,100 standard pages ⁶ Yellow: 10,100 standard pages ⁶ Black: 10,700 standard pages ⁶	106R03768 106R03767 106R03766 106R03765
CMYK Drum Cartridge	82,200 standard pages ⁷	113R00782
Waste Toner Bottle	21,200	115R00129
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964
ACCESSORIES / OPTIONS		
Single Tray Module (does not include stand)		097S04910
Single Tray with Stand Module		097S04907
Three Tray Module		097S04908
Envelope Tray (This replaces Tray 1)		497K17720
Integrated Office Finisher		097S04911
HDD (320 GB hard drive) (Optional)		497K17740
Wireless Network Adapter Kit		497K16750

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.